

# US 2-PIN POWER SUPPLY, 18 W



## TECHNICAL DATA

### GENERAL

|                                  |                 |
|----------------------------------|-----------------|
| Input voltage                    | 100 – 240 VAC   |
| Input frequency                  | 50 / 60 Hz      |
| Input current                    | 0.6 A           |
| Output voltage                   | 12 VDC          |
| Output current                   | 1.5 A           |
| Input voltage absolute maximum   | 90 – 264 VAC    |
| Input frequency absolute maximum | 47 – 63 Hz      |
| Inrush current                   | 60 A            |
| Output voltage absolute maximum  | 11.4 – 12.6 VDC |

|                                   |                                |
|-----------------------------------|--------------------------------|
| Short circuit protection          | ✓                              |
| HIPOT (dielectric withstand test) | Primary to Secondary: 4242 VDC |
| MTBF                              | 50000 h                        |
| Input connector                   | US (Type A)                    |
| Output connector                  | 2-pin, with cord end terminals |
| Weight                            | 106 g                          |

Certification **Safety:** CSA C22.2 No. 62368-1-14, 2nd Ed.  
**EMC:** FCC Part 15, Subpart B: 2023,  
ANSI C63.4:2014 ammended as per ANSI C63.4:2017

